

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

SECTION 1: Identification

1.1 Product identifier

Trade name

Cut and Finish

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Vehicle polishing compound
Professional use
Industrial use

HS code

3405.30.00.

1.3 Details of the supplier of the safety data sheet

Wisconsin Chemical Wholesale
385 W Arndt St
Fond Du lac, WI 54935
United Statese-mail: wisconsinchemicalwholesale@gmail.com
Website: www.wisconsinchemical.com**e-mail (competent person)****wisconsinchemicalwholesale@gmail.com**

1.4

Emergency telephone number
Emergency information serviceUSA 1.800.535.5053, INTL 1.352.323.3500
24 hr emergency information

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification.

The most important adverse physicochemical, human health and environmental effects

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

Additional information

Contains a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word not required

- Pictograms not required

2.3 Other hazards

Special danger of slipping by leaking/spilling product. There is no additional information.

Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Results of PBT and vPvB assessment

 Contains a PBT-substance at a concentration of $\geq 0.1\%$. Contains a vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

 Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS				
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
decamethylcyclopentasiloxane	CAS No 541-02-6	10 – <25	Flam. Liq. 4 / H227	PBT vPvB
C9-C15 mixed cycloalkanes and alkanes	CAS No 64742-47-8	5 – <10	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 4 / H227	
White mineral oil (petroleum)	CAS No 8042-47-5	1 – <5	Asp. Tox. 1 / H304	

Notes

PBT: The substance was identified as a PBT (persistent, bioaccumulative and toxic)

vPvB: The substance was identified as a vPvB (very persistent and very bioaccumulative)

Remarks

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

none

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	alpha-alumina	1344-28-1	REL							appx-D	NIOSH REL
US	alpha-alumina	1344-28-1	PEL		15					dust	29 CFR 1910.1000
US	alpha-alumina	1344-28-1	PEL		5					r	29 CFR 1910.1000
US	aluminium, insoluble compounds	1344-28-1	TLV®		1					r	AC-GIH® 2019
US	aluminium oxide	1344-28-1	PEL (CA)		10					dust	Cal/O SHA PEL
US	aluminium oxide	1344-28-1	PEL (CA)		5					r	Cal/O SHA PEL
US	mineral oil	8042-47-5	TLV®		5					i, ex-Met-Work Fl	AC-GIH® 2019

Notation

appx-D see Appendix D - Substances with No Established RELS
 Ceiling-C ceiling value is a limit value above which exposure should not occur
 dust as dust

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Notation

exMetWork-excluding metal working fluids FI

i

r inhalable fraction

STEL respirable fraction

TWA short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified)

Relevant DNELs of components						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
White mineral oil (petroleum)	8042-47-5	DNEL	165 mg/m ³	human, dermal	worker (industry)	chronic - systemic effects
White mineral oil (petroleum)	8042-47-5	DNEL	217 mg/kg bw/day		worker (industry)	chronic - systemic effects

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Relevant PNECs of components						
Name of substance	CAS No	End-point	Threshold level	Organisms	Environmental compartment	Exposure time
pentasiloxane				isms		instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	2.5 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	turquoise
Particle	not relevant (liquid)
Odor	sweet - mint

Other safety parameters

pH (value)	8 – 8.5 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	>100 °C at 101 Pa

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.8 vol%
- Upper explosion limit (UEL)	6 vol%
Vapor pressure	32 hPa at 25 °C
Density	1.1 – 1.1 g/ml
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>220 °C (auto-ignition temperature (liquids and gases))

Viscosity

- Kinematic viscosity	5,000 cSt
- Dynamic viscosity	5,392 cP
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification.

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
decamethylcyclopentasiloxane	541-02-6	dermal	>2,000 mg/kg
decamethylcyclopentasiloxane	541-02-6	inhalation: dust/mist	8.7 mg/l/4h
C9-C15 mixed cycloalkanes and alkanes	64742-47-8	dermal	>2,000 mg/kg
White mineral oil (petroleum)	8042-47-5	dermal	>2,000 mg/kg
White mineral oil (petroleum)	8042-47-5	inhalation: dust/mist	>5 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h
White mineral oil (petroleum)	8042-47-5	LL50	>10,000 mg/l	fish	96 h

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Contains a PBT-substance at a concentration of $\geq 0.1\%$. Contains a vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

Waste treatment methods

13.1

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 3082
Not regulated under DOT until packaged in single containers larger than 119 gallons each (liquid) or 882 lbs each (solid).	
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

DOT	Environmentally hazardous substance, liquid, n.o.s.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
Technical name (hazardous ingredients)	decamethylcyclopentasiloxane, peppermint oil

14.3 Transport hazard class(es)

DOT	9
IMDG-Code	9
ICAO-TI	9

14.4 Packing group

DOT	III III III
IMDG-Code	hazardous to the aquatic environment
ICAO-TI	decamethylcyclopentasiloxane, peppermint oil

14.5 Environmental hazards

Environmentally hazardous substance (aquatic environment)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Particulars in the shipper's declaration UN3082, Environmentally hazardous substance, liquid, n.o.s., (contains: decamethylcyclopentasiloxane, peppermint oil), 9, III

Danger label(s) 9, fish and tree



Environmental hazards yes (hazardous to the aquatic environment)

Special provisions (SP) 8, 146, 173, 335, IB3, T4, TP1, TP29

ERG No 171

International Maritime Dangerous Goods Code (IMDG)

Marine pollutant yes (hazardous to the aquatic environment) (decamethylcyclopentasiloxane)

Danger label(s) 9, fish and tree



Special provisions (SP) 274, 335, 969

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-A, S-F

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR)

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 9, fish and tree



Special provisions (SP) A97, A158, A197

Excepted quantities (EQ) E1

Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
aluminium oxide	1344-28-1	abrasive	
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
C9-C15 mixed cycloalkanes and alkanes	64742-47-8	solvents	
polydimethylsiloxane	63148-62-9	surface modifier	
White mineral oil (petroleum)	8042-47-5	lubricant	
carnauba wax	8015-86-9	wax	
polytrimethylhydrosilylsiloxane	68988-56-7	surface modifier	
polyacrylamide	9003-05-8	viscosity modifier	
Methyl ester of rosin, partially hydrogenated, Me esters	8050-15-5	fragrance	
ethoxylated C11-15 secondary alcohols	68131-40-8	surfactant	
Alcohols, C11-15- secondary, ethoxylated	84133-50-6	surfactant	
menthone	89-80-5 10458-14-7 1074-95-9	fragrance	
peppermint oil	8006-90-4 84082-70-2	fragrance	
tetra(trimethylsiloxy)silane	3555-47-3	surface modifier	Canada PBiTs

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 8.5 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 8.6 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Category	Rating	Description
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
 Flammability: flammability hazards
 Health: health hazard
 Personal protection: personal protective equipment (PPE) for normal use
 Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL ENCS	not all ingredients are listed
JP	ISHA ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Legend

CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

Additional information

The contained substances are listed in the following national inventories:

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").
 Restructuring: section 9, section 14

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Abbr.	Descriptions of used abbreviations
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT-SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

CUT AND FINISH

Version number: 1.0

Date of compilation: 2025-02-12

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IM-DG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.